



COMPACT 200 UM

Exit luminaire in compliance with EN 60598-1/2-22 and EN 1838.

Extremely slim housing made of anodized extruded aluminum with screwless caps. Universal mounting for wall and ceiling installation by turning the upper luminaire profile.

The luminaire price includes one pictogram foil set - arrow left/right/down/up/blind (Visibility distance 23 m).

The 10 mm light deflecting pane is illuminated with a 1 watt or 2 watt LED-bar.


Technical specifications

Luminaire type	Luminaires for central battery systems		Self contained luminaires	
Illuminant	1 W LED-bar	2 W LED-bar	1 W LED-bar	2 W LED-bar
Visibility distance	23 m			
Connecting terminals	3 x 2.5 mm² for double assignment			
Colour	white aluminum (silver)			
Material	Aluminum			
Mounting type	Wall-/ceiling mounting			
Additional mounting types*	Ceiling mounting (wire suspension), Pendulum mounting			
Dimensions (W x H x D)	DM 256 x 189 x 35 mm WM 256 x 187 x 37 mm			
Pane dimensions (W x H x D)	248 x 148 x 10 mm			
Protection class	IP40			
Safety class	I			
IK Safety class	IK03			
Light current (mains)	130 lm	260 lm	130 lm	260 lm
Luminous flux				
Emergency (DC) / mains				
Battery duration 1h	–	–	50% / 100%	30% / 100%
Battery duration 3h	–	–	50% / 100%	30% / 100%
Battery duration 8h	–	–	25% / 100%	15% / 100%
Power consumption	4.5 VA	5.5 VA	4.5 VA	5.5 VA
Battery current input	11 mA	14 mA	–	
Battery duration	–		1h / 3h / 8h	
Battery operation				
Voltage supply	230V 50/60Hz; 220V DC +25/-20%		230V 50/60Hz	
NiMH-battery				
Battery duration 1h	–	–	4,8V 0,8Ah	4,8V 0,8Ah
Battery duration 3h	–	–	4,8V 0,8Ah	4,8V 0,8Ah
Battery duration 8h	–	–	4,8V 0,8Ah	4,8V 0,8Ah
Temperature range	-10°C to +40°C		–	
Non-maintained mode	–		0°C to +35°C	
Maintained mode	–		-5°C to +30°C	
optional				
Multi-switch and monitoring module	ELC MSÜ3 SET009 SET010		–	
Self monitoring	–		SELF CHECK	
Central monitoring	–		SAFELOG Line	
Wireless monitoring	–		SAFELOG Wireless	


* Optional accessory required



Ceiling mounting



Wall mounting



Pictogram-set - included in the delivery



Optional pictograms (-sets)



Accessories

Wire guard
Universal cover plate
Cable surface mounting set
Chain assembly set
Central pendulum - Aluminum/Plastic
Central pendulum - Plastic
Cable assembly set
Pictograms