



REPEATER WIRELESS


Extension module for SAFELOG Wireless SWX

Compact repeater with integrated antenna, made of white polycarbonate for ceiling and wall mounting. The use of the repeater increases the range of the wireless network within a property and stabilises communication. Data is exchanged via wireless in a 868 MHz band.

The repeater is additionally equipped with a back-up battery, which guarantees a back-up time of up to 8 hours in the event of a power failure and thus ensures communication in the wireless network.

Equipment

- Fully automatic wireless network building (Meshing)
- Integrated status indicator
- In case of power failure, communication up to 8 hours possible (Backup-Battery)



Technical specifications and order information

REPEATER-Wireless SAFELOG SWX

Connecting terminals	1.5 mm ² to 2.5 mm ²
Colour	white
Material	Polycarbonate
Mounting type	Wall-/ceiling mounting
Dimensions (W x H x D)	125 x 38 x 125 mm
Frequency range	863 – 870 MHz (SRD Band)
Wireless range	max. 30 m with direct visual contact
Power consumption	5,0 W
Power supply	1/N/PE AC 50Hz 230V
Ambient temperature	-5°C to +35°C
Storage temperature	0°C to +30°C
Protection class	IP40
Safety class	I

Order number 910023

Suitable for following systems:

SAFELOG TOUCH WIRELESS SAFELOG mini

