



LBOARD E300 DE

Exit luminaire EN IEC 60598-1/2-22, EN 1838, DIN 4844-1.

Housing made from steel sheeting, powder coated in white.

Available for recessed ceiling mounting with 10 mm thick light-deflecting pane and replaceable pictograms.


The luminaire price includes per luminaire one pictogramfoil set - arrow left/right/down/up/blind (Visibility distance 30 m).

Optionally available with 1.5 or 3 Watt LED-bar.



Technical specifications

Luminaire type	Luminaires for central battery systems		Self contained luminaires	
Illuminant	1.5 W LED-bar	3 W LED-bar	1.5 W LED-bar	3 W LED-bar
Visibility distance	30 m			
Luminance	DIN 4844-1 > 500 cd/m²			
Connecting terminals	3 x 2.5 mm² for double assignment			
Colour	white			
Material	Sheet steel			
Mounting type	Recessed mounting			
Dimensions (W x H x D)	DE 401 x 241 x 74 mm			
Pane dimensions (W x H x D)	324 x 187.5 x 10 mm			
Dimensions ceiling cutout (L x W)	min. 386 x 62 mm / max. 390 x 65 mm			
Installation depth	98 mm			
Protection class	IP40			
Safety class	I			
IK Safety class	IK03			
Light current (mains)	190 lm	350 lm	190 lm	350 lm
Luminous flux				
Emergency (DC) / mains				
Battery duration 1h	–	–	40% / 100%	20% / 100%
Battery duration 3h	–	–	40% / 100%	20% / 100%
Battery duration 8h	–	–	20% / 100%	10% / 100%
Power consumption	5 VA	6 VA	5 VA	6 VA
Battery current input	12 mA	19 mA	–	
Battery duration				
Battery operation	–		1h / 3h / 8h	
Voltage supply	230V 50/60Hz; 220V DC +25/-20%		230V 50/60Hz	
NiMH-battery				
Battery duration 1h	–	–	4,8V 0,8Ah	4,8V 0,8Ah
Battery duration 3h	–	–	4,8V 0,8Ah	4,8V 0,8Ah
Battery duration 8h	–	–	4,8V 0,8Ah	4,8V 0,8Ah
Temperature range	-10°C to +40°C		–	
Non-maintained mode	–		0°C to +35°C	
Maintained mode	–		-5°C to +30°C	
optional				
Multi-switch and monitoring module	DALI ELC MSÜ3 SET009 SET010/025		–	
Self monitoring	–		SELF CHECK	
Central monitoring	–		SAFELOG Line	
Wireless monitoring	–		SAFELOG Wireless	



Pictogram-set - included in the delivery



Optional pictograms (-sets)



Accessories

Cement assembly box
Pictograms