



KBOX 200 UM

Exit luminaire in compliance with EN 60598-1/2-22 and EN 1838.

Modern IP54 escape sign luminaire made of white polycarbonate for universal mounting.

Simple, tool-free mounting with click system.

The luminaire can be used for single-sided wall mounting, double-sided ceiling mounting or bracket mounting. For wall mounting, the installation is done via a fixed enclosed back plate, for ceiling and bracket mounting via a click adapter, which is enclosed with the luminaire.

In addition, the luminaire has light emission windows facing downwards.

The luminaire price includes one pictogram set - arrow left/right/down/up/blind (Visibility distance 23 m).


The luminaire is equipped with a 1 Watt LED-bar.




Technical specifications

Luminaire type	Luminaires for central battery systems	Self contained luminaires
Illuminant	1 W LED-bar	1 W LED-bar
Visibility distance	23 m	
Connecting terminals	2 x 2.5 mm ² for double assignment	
Colour	white	
Material	Polycarbonate	
Mounting type	Wall-/ceiling mounting, wall bracket mounting	
Dimensions (W x H x D)	DM 250 x 156 x 80 mm	
	WM 250 x 135 x 82 mm	
	ALM 271 x 135 x 80 mm	
Protection class	IP54	
Safety class	II	
IK Safety class	IK03	
Light current (mains)	130 lm	130 lm
Luminous flux		
Emergency (DC) / mains		
Rated operating time 1h	-	50% / 100%
Rated operating time 3h	-	50% / 100%
Rated operating time 8h	-	25% / 100%
Power consumption	4.5 VA	4.5 VA
Battery current input	11 mA	-
Battery duration	-	1h / 3h / 8h
Battery operation	-	-
Voltage supply	230V 50/60Hz; 220V DC +25/-20%	230V 50/60Hz
NiMH-battery		
Rated operating time 1h	-	4,8V 0,8Ah
Rated operating time 3h	-	4,8V 0,8Ah
Rated operating time 8h	-	4,8V 0,8Ah
Temperature range	-10°C to +40°C	-
Non-maintained mode	-	0°C to +35°C
Maintained mode	-	-5°C to +30°C
optional		
Multi-switch and monitoring module	DALI ELC MSÜ3 SET009 SET010	-
Self monitoring	-	SELF CHECK
Central monitoring	-	SAFELOG Line
Wireless monitoring	-	SAFELOG Wireless


Ceiling mounting



Wall mounting



Bracket mounting



Pictogram-set - included in the delivery



Optional pictograms (-sets)



Accessories

Wire guard

Universal cover plate

Chain assembly set

Central pendulum - Plastic

Cable assembly set

Pictograms