10m | IP54 | 1W LED | Colour

L-PLAST 100 WM

MADE in GERMANY


Exit luminaire EN IEC 60598-1/2-22, EN 1838, DIN 4844-1.
Polycarbonate housing with clear luminaire cover for one-sided pictogram equipment for wall mounting.
The luminaire price includes one pictogramfoil set - arrow left/right/down/up (Visibility distance 10 m).
The luminaire is supplied with a 1 Watt LED-bar.




Technical specifications

Luminaire type	Luminaires for central battery systems	Self contained luminaires
Illuminant	1 W LED-bar	1 W LED-bar
Visibility distance	10 m	
Luminance	DIN 4844-1 > 500 cd/m²	
Connecting terminals	2 x 2.5 mm² for double assignment	
Colour	white	
Material	Polycarbonate (light cover clear)	
Mounting type	Wall mounting	
Dimensions (W x H x D)	WM 239 x 62 x 59 mm	
Protection class	IP54	
Safety class	II	
IK Safety class	IK03	
Light current (mains)	130 lm	130 lm
Luminous flux Emergency (DC) / mains		
Battery duration 1h	–	50% / 100%
Battery duration 3h	–	50% / 100%
Battery duration 8h	–	25% / 100%
Power consumption	4.5 VA	4.5 VA
Battery current input	11 mA	–
Battery duration Battery operation	–	1h / 3h / 8h
Voltage supply	230V 50/60Hz; 220V DC +25/-20%	230V 50/60Hz
NiMH-battery		
Battery duration 1h	–	4,8V 0,8Ah
Battery duration 3h	–	4,8V 0,8Ah
Battery duration 8h	–	4,8V 0,8Ah
Temperature range	-10°C to +40°C	–
Non-maintained mode	–	0°C to +35°C
Maintained mode	–	-5°C to +30°C
optional		
Multi-switch and monitoring module	ELC MSÜ3 SET009 SET010	–
Self monitoring	–	SELF CHECK
Central monitoring	–	SAFELOG Line
Wireless monitoring	–	SAFELOG Wireless

Wall mounting





Pictogram-set - included in the delivery



Accessories

Wire guard

Technical changes reserved / 04.11.2026