



SAFE W-2F

Safety luminaire in compliance with EN IEC 60598-1/2-22 and EN 1838.

Weather-proof housing made of aluminum die-casting with a pane of safety glass, sealed with silicone.

Cable inlet into the luminaire possible from the back and from below.

Model for wall mounting with two high-performance LEDs and cast acrylic optics for escape route illumination by means of circular, light-deflecting characteristics. Product includes an IP65 membrane pressure compensation valve.

Optionally, the luminaire can be delivered as a central battery version for a temperature range down to -35°C (unmonitored).

Optional the luminaire is available with an external supply unit to mount it outside and the supply unit inside. Also optional is a heating case with battery (4,8V 4,2Ah) to use in environments with lowest permissible temperature of -20°C within the luminaire.




Figure shows accessory

Technical specifications

Luminaire type	Luminaires for central battery systems	Self contained luminaires
Illuminant	2 x 3 W LED	2 x 3 W LED
Connecting terminals	3 x 2.5 mm ² for double assignment	
Colour	white / graphite grey	
Material	Aluminum die-cast	
Mounting type	Wall mounting	
Dimensions (W x H x D)	WM 190 x 190 x 115 mm	
Protection class	IP65	
Safety class	I	
IK Safety class	IK08	
Light current (mains)	480 lm	360 lm
Light current (emergency)		
Battery duration 1h	–	480 lm
Battery duration 3h	–	480 lm
Battery duration 8h	–	240 lm
Luminous flux		
Emergency (DC) / mains		
Battery duration 1h	–	100% / 75%
Battery duration 3h	–	100% / 75%
Battery duration 8h	–	50% / 75%
Power consumption	10 VA	8 VA
Battery current input	25 mA	–
Battery duration		
Battery operation	–	1h / 3h / 8h
Voltage supply	230V 50/60Hz; 220V DC +25/-20%	230V 50/60Hz
NiMH-battery		
Battery duration 1h	–	4,8V 2,0Ah 4,8V 2,0Ah + AkH
Battery duration 3h	–	4,8V 4,2Ah 4,8V 4,2Ah + AkH
Battery duration 8h	–	4,8V 4,2Ah 4,8V 4,2Ah + AkH
Temperature range	-10°C to +40°C (monitored) / -20°C to +40°C (unmonitored)	–
Non-maintained mode	–	0°C to +35°C
Maintained mode	–	-5°C to +30°C
optional		
Multi-switch and monitoring module	ELC MSÜ3 SET009 SET010/025	–
Self monitoring	–	SELF CHECK
Central monitoring	–	SAFELOG Line
Wireless monitoring	–	SAFELOG Wireless

Wall mounting



Accessories


Rear mounting bracket

Bollard

Ground anchor for bollard

Pole and wall bracket


Lighting data and tables of luminaire distances ($E = 1,25 \text{ lx}$)



Wall mounting


Luminaires for central battery systems wide area optics

Distance table for plane emergency routes / distance data in meters




Self contained luminaires wide area optics


Distance table for plane emergency routes / distance data in meters



Self contained luminaires wide area optics

Distance table for plane emergency routes / distance data in meters





Luminous flux emergency / mains: 240lm/360lm – **Battery duration: 8h**

t = 1.00	h	1.00	2.00	2.50	3.00	3.50	4.00	4.50	5.00
	a	6.00	9.00	10.00	10.50	11.00	11.50	11.50	11.00
	b	2.70	4.00	4.00	4.00	4.00	3.50	3.50	3.50
t = 2.00	h	1.00	2.00	2.50	3.00	3.50	4.00	4.50	5.00
	a	6.30	9.00	10.00	10.50	11.00	11.00	10.50	10.50
	b	2.70	3.50	3.50	3.50	3.50	3.50	3.00	3.00
t = 3.00	h	1.00	2.00	2.50	3.00	3.50	4.00	4.50	5.00
	a	4.80	7.50	8.50	9.00	9.50	9.50	10.00	9.50
	b	1.00	2.50	3.00	3.00	3.00	2.50	2.50	2.00

t = distance to escape middle