



# L-PLAST 100 WM

## Exit luminaire in compliance with EN 60598-1/2-22 and EN 1838.

Polycarbonate housing with clear luminaire cover for one-sided pictogram equipment for wall mounting.

The luminaire price includes one pictogramfoil set - arrow left/right/down (Visibility distance 10 m).

The luminaire is supplied with a 1 Watt LED-bar.



## Technical specifications

Luminaire type	Luminaires for central battery systems	Self contained luminaires
Illuminant	1 W LED-bar	1 W LED-bar
Visibility distance	10 m	
Connecting terminals	2 x 2.5 mm <sup>2</sup> for double assignment	
Colour	white	
Material	Polycarbonate (light cover clear)	
Mounting type	Wall mounting	
Dimensions (W x H x D)	WM 239 x 62 x 59 mm	
Protection class	IP54	
Safety class	II	
IK Safety class	IK03	
Light current (mains)	130 lm	130 lm
Luminous flux		
Emergency (DC) / mains		
Rated operating time 1h	-	50% / 100%
Rated operating time 3h	-	50% / 100%
Rated operating time 8h	-	25% / 100%
Power consumption	4.5 VA	4.5 VA
Battery current input	11 mA	-
Battery duration	-	1h / 3h / 8h
Battery operation		
Voltage supply	230V 50/60Hz; 220V DC +25/-20%	230V 50/60Hz
NiMH-battery		
Rated operating time 1h	-	4,8V 0,8Ah
Rated operating time 3h	-	4,8V 0,8Ah
Rated operating time 8h	-	4,8V 0,8Ah
Temperature range	-10°C to +40°C	-
Non-maintained mode	-	0°C to +35°C
Maintained mode	-	-5°C to +30°C
optional		
Multi-switch and monitoring module	ELC MSÜ3 SET009 SET010	-
Self monitoring	-	SELF CHECK
Central monitoring	-	SAFELOG Line
Wireless monitoring	-	SAFELOG Wireless

## Pictogram-set - included in the delivery



## Accessories

Wire guard

## Wall mounting

