



H-LINE 200 UM

Exit luminaire in compliance with EN 60598-1/2-22 and EN 1838.


Slim polycarbonate housing with narrow, transparent cover for pictograms to be inserted on both sides for universal mounting. Optionally usable for wall or ceiling mounting due to pre-stamped mounting and cable entry openings from above or behind. Screwless, easy-to-use locking mechanism. With optional recessed ceiling frame also available as recessed ceiling version. The luminaire is available with a 1 or 2 watt LED-bar and is supplied with a set of interchangeable pictogram foils - arrow left/right/down/up/blind (Visibility distance 23 m).




Technical specifications

Luminaire type	Luminaires for central battery systems		Self contained luminaires	
	1 W LED-bar	2 W LED-bar	1 W LED-bar	2 W LED-bar
Illuminant				
Visibility distance	23 m			
Connecting terminals	2 x 2.5 mm ² for double assignment			
Colour	white			
Material	Polycarbonate (light cover clear)			
Mounting type	Wall-/ceiling mounting			
Dimensions (W x H x D)	WM/DM 265 x 184 x 37 mm			
Protection class	IP43			
Safety class	II			
IK Safety class	IK03			
Light current (mains)	130 lm	260 lm	130 lm	260 lm
Luminous flux				
Emergency (DC) / mains				
Rated operating time 1h	-	-	50% / 100%	30% / 100%
Rated operating time 3h	-	-	50% / 100%	30% / 100%
Rated operating time 8h	-	-	25% / 100%	15% / 100%
Power consumption	4.5 VA	5.5 VA	4.5 VA	5.5 VA
Battery current input	11 mA	14 mA	-	
Battery duration	-			
Battery operation	1h / 3h / 8h			
Voltage supply	230V 50/60Hz; 220V DC +25/-20%		230V 50/60Hz	
NiMH-battery				
Rated operating time 1h	-	-	4,8V 0,8Ah	4,8V 0,8Ah
Rated operating time 3h	-	-	4,8V 0,8Ah	4,8V 0,8Ah
Rated operating time 8h	-	-	4,8V 0,8Ah	4,8V 0,8Ah
Temperature range	-10°C to +40°C		-	
Non-maintained mode	-		0°C to +35°C	
Maintained mode	-		-5°C to +30°C	
optional				
Multi-switch and monitoring module	ELC MSÜ3 SET009 SET010		-	
Self monitoring	-		SELF CHECK	
Central monitoring	-		SAFELOG Line	
Wireless monitoring	-		SAFELOG Wireless	

Ceiling mounting



Wall mounting



Pictogram-set - included in the delivery



Optional pictograms (-sets)



Accessories

Wire guard

Cement assembly box

Recessed ceiling frame - clampable

Universal cover plate

Chain assembly set

Double pendulum set with long canopy

Central pendulum sets with long canopy

Central pendulum - Plastic

Wire sets with long canopy

Cable assembly set

Wall bracket

Pictograms