



COMPACT 300 UM

Exit luminaire in compliance with EN 60598-1/2-22 and EN 1838.

Extremely slim housing made of anodized extruded aluminum with screwless caps. Universal mounting for wall and ceiling installation by turning the upper luminaire profile.

The luminaire price includes one pictogram foil set - arrow left/right/down/up/blind (Visibility distance 30 m).


The 10 mm light deflecting pane is illuminated with a 1,5 watt or 3 watt LED-bar.




Technical specifications

Luminaire type	Luminaires for central battery systems		Self contained luminaires	
	1.5 W LED-bar	3 W LED-bar	1.5 W LED-bar	3 W LED-bar
Illuminant				
Visibility distance	30 m			
Connecting terminals	3 x 2.5 mm ² for double assignment			
Colour	white aluminum (silver)			
Material	Aluminum			
Mounting type	Wall-/ceiling mounting			
Dimensions (W x H x D)	DM 332 x 228 x 35 mm WM 332 x 226 x 37 mm			
Pane dimensions (W x H x D)	324 x 187.5 x 10 mm			
Protection class	IP40			
Safety class	I			
IK Safety class	IK03			
Light current (mains)	190 lm	350 lm	190 lm	350 lm
Luminous flux Emergency (DC) / mains				
Rated operating time 1h	-	-	40% / 100%	20% / 100%
Rated operating time 3h	-	-	40% / 100%	20% / 100%
Rated operating time 8h	-	-	20% / 100%	10% / 100%
Power consumption	5 VA	6 VA	5 VA	6 VA
Battery current input	12 mA	19 mA	-	
Battery duration	-		1h / 3h / 8h	
Battery operation				
Voltage supply	230V 50/60Hz; 220V DC +25/-20%		230V 50/60Hz	
NiMH-battery				
Rated operating time 1h	-	-	4,8V 0,8Ah	4,8V 0,8Ah
Rated operating time 3h	-	-	4,8V 0,8Ah	4,8V 0,8Ah
Rated operating time 8h	-	-	4,8V 0,8Ah	4,8V 0,8Ah
Temperature range	-10°C to +40°C		-	
Non-maintained mode	-		0°C to +35°C	
Maintained mode	-		-5°C to +30°C	
optional				
Multi-switch and monitoring module	ELC MSÜ3 SET009 SET010		-	
Self monitoring	-		SELF CHECK	
Central monitoring	-		SAFELOG Line	
Wireless monitoring	-		SAFELOG Wireless	

Ceiling mounting



Wall mounting



Pictogram-set - included in the delivery



Optional pictograms (-sets)



Accessories

Wire guard

Universal cover plate

Cable surface mounting set

Chain assembly set

Central pendulum - Aluminum/Plastic

Central pendulum - Plastic

Cable assembly set

Pictograms