
IP43 | 2W LED | Colour

S-LINE 200 BEL WM/DM

MADE in GERMANY

Safety luminaire in compliance with EN IEC 60598-1/2-22 and EN 1838.
Extremely slim, attractive housing made of polycarbonate in white or black with clear hood. Screwless, easy-to-use locking mechanism.
Can be used for wall or ceilling mounting. With optional recessed ceiling frame also available as recessed ceiling version. Luminaire for area illumination.
The luminaire is equipped with a 2 Watt LED-bar.




Technical specifications

Luminaire type	Luminaires for central battery systems	Self contained luminaires
Illuminant	2 W LED-bar	2 W LED-bar
Connecting terminals	2 x 2.5 mm² for double assignment	
Colour	white / black	
Material	Polycarbonate (light cover clear)	
Mounting type	Wall-/ceiling mounting	
Additional mounting types*	Recessed mounting, Ceiling mounting (wire suspension)	
Dimensions (W x H x D)	WM/DM 265 x 69 x 37 mm	
Protection class	IP43	
Safety class	II	
IK Safety class	IK03	
Light current (mains)	240 lm	240 lm
Light current (emergency)		
Battery duration 1h	–	240 lm
Battery duration 3h	–	105 lm
Luminous flux Emergency (DC) / mains		
Battery duration 1h	–	100% / 100%
Battery duration 3h	–	45% / 100%
Power consumption	5.5 VA	5.5 VA
Battery current input	14 mA	–
Battery duration Battery operation	–	1h / 3h
Voltage supply	230V 50/60Hz; 220V DC +25/-20%	230V 50/60Hz
NiMH-battery		
Battery duration 1h	–	4,8V 0,8Ah
Battery duration 3h	–	4,8V 0,8Ah
Temperature range	-10°C to +40°C	–
Non-maintained mode	–	0°C to +35°C
Maintained mode	–	-5°C to +30°C
optional		
Multi-switch and monitoring module	ELC MSÜ3 SET009 SET010	–
Self monitoring	–	SELF CHECK
Central monitoring	–	SAFELOG Line
Wireless monitoring	–	SAFELOG Wireless

* Optional accessory required

Wall-/ceiling mounting




Accessories

Wire guard
Cement assembly box
Recessed ceiling frame - clampable
Universal cover plate
Chain assembly set
Cable assembly set

Technical changes reserved / 04.11.2026

Lighting data and tables of luminaire distances (E = 1,25 lx)




Ceiling mounting

Luminaires for central battery systems **Wide area illumination**

Distance table for plane emergency routes / distance data in meters

Illuminant: 2W LED-bar




Luminous flux emergency / mains: 240lm

h	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00
a	6.80	7.50	7.80	8.60	8.90	9.20	9.40	9.60	9.70	9.80
b	1.80	1.90	1.90	1.90	1.80	1.70	1.60	1.40	1.20	0.70
c	7.40	7.80	8.40	8.90	9.30	9.50	9.80	10.00	10.00	10.00
d	1.90	1.90	2.00	2.00	1.70	1.60	1.60	1.60	1.20	0.70

Self contained luminaires **Wide area illumination**

Distance table for plane emergency routes / distance data in meters

Illuminant: 2W LED-bar




Luminous flux emergency / mains: 240lm/240lm – **Battery duration: 1h**

h	2.50	3.00	3.50	4.00	4.50	5.00	5.50	6.00	6.50	7.00
a	6.80	7.50	7.80	8.60	8.90	9.20	9.40	9.60	9.70	9.80
b	1.80	1.90	1.90	1.90	1.80	1.70	1.60	1.40	1.20	0.70
c	7.40	7.80	8.40	8.90	9.30	9.50	9.80	10.00	10.00	10.00
d	1.90	1.90	2.00	2.00	1.70	1.60	1.60	1.60	1.20	0.70

Self contained luminaires **Wide area illumination**

Distance table for plane emergency routes / distance data in meters

Illuminant: 2W LED-bar



Luminous flux emergency / mains: 105lm/240lm – **Battery duration: 3h**

h	2.50	3.00	3.50	4.00	4.50
a	5.30	5.90	6.20	6.10	6.50
b	1.20	1.20	1.10	0.90	0.60
c	5.80	6.10	6.40	6.60	6.70
d	1.30	1.10	1.10	1.00	0.60