



SMARTLUX 200 DM

Exit luminaire EN IEC 60598-1/2-22, EN 1838, DIN 4844-1.

Elegant, modern IP54 escape sign luminaire made of white polycarbonate with clear cover and simple, screwless mounting by click system.

Luminaire for pictograms on both sides for ceiling mounting.

The luminaire price includes one pictogram foil set - arrow left/right/down/up/blind (Visibility distance 23 m).

The luminaire is equipped with a 2 Watt LED-bar.




Technical specifications

Luminaire type	Luminaires for central battery systems	Self contained luminaires
Illuminant	2 W LED-bar	2 W LED-bar
Visibility distance	23 m	
Luminance	DIN 4844-1 > 500 cd/m²	
Connecting terminals	2 x 2.5 mm² for double assignment	
Colour	white	
Material	Polycarbonate (light cover clear)	
Mounting type	Ceiling mounting	
Additional mounting types*	wall bracket mounting, Ceiling mounting (wire suspension), Pendulum mounting	
Dimensions (W x H x D)	DM 243 x 149 x 62 mm	
Protection class	IP54	
Safety class	II	
IK Safety class	IK03	
Light current (mains)	240 lm	240 lm
Luminous flux	–	30% / 100%
Emergency (DC) / mains		
Battery duration 1h		
Battery duration 3h		
Battery duration 8h	–	15% / 100%
Power consumption	5.5 VA	5.5 VA
Battery current input	14 mA	–
Battery duration	–	1h / 3h / 8h
Battery operation		
Voltage supply	230V 50/60Hz; 220V DC +25/-20%	230V 50/60Hz
NiMH-battery	–	4,8V 0,8Ah
Battery duration 1h		
Battery duration 3h		
Battery duration 8h		
Temperature range	-10°C to +40°C	–
Non-maintained mode	–	0°C to +35°C
Maintained mode	–	-5°C to +30°C
optional		
Multi-switch and monitoring module	DALI ELC MSÜ3 SET009 SET010	–
Self monitoring	–	SELF CHECK
Central monitoring	–	SAFELOG Line
Wireless monitoring	–	SAFELOG Wireless

* Optional accessory required

Ceiling mounting



Pictogram-set - included in the delivery



Optional pictograms (-sets)



Accessories

Universal cover plate	
Chain assembly set	
Central pendulum - Plastic	
Cable assembly set	
Wall bracket	
Pictograms	